



ATTORNEYS AT LAW

1940 DUKE STREET  
ALEXANDRIA, VIRGINIA 22314  
USA

(703) 413-3000  
(703) 413-2220 FACSIMILE

OBLONPAT@OBLON.COM

PATENT, TRADEMARK AND COPYRIGHT LAW  
AND RELATED FEDERAL AND ITC LITIGATION

WWW.OBLON.COM

**FACSIMILE**

PLEASE CALL US AT (703) 413-3000 IF THE MESSAGE YOU RECEIVE IS INCOMPLETE OR NOT LEGIBLE

<b>TO</b> NAME <u>Examiner John TERESINSKI</u> COMPANY/FIRM <u>USPTO</u> NUMBER OF PAGES INCLUDING COVER: <u>4</u>	DATE <u>6/9/04</u> FAX # <u>571-273-2235</u> CONFIRM FAX: <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO
<b>FROM</b> NAME <u>Chien Yuan</u> DIRECT PHONE # <u>703-412-3536</u>	<u>220445US2X</u> OUR REFERENCE <u>10/092,993</u> YOUR REFERENCE

**MESSAGE**

Please see the attached claim amendments as we discussed.

\*\*\*\*\*COMMUNICATIONS FAX OVER DIRECT FOR FIRM USE ONLY\*\*\*\*\*

Unless otherwise indicated or obvious from the nature of the transmittal, the information contained in this facsimile message is attorney privileged and confidential information intended for the use of the individual or entity named above. If the reader of this message is not the intended recipient or the employee or agent responsible to deliver it to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this communication in error or are not sure whether it is privileged, please immediately notify us by telephone and return the original message to us at the above address via the U.S. Postal Service at our Expense. Thank You.

U.S. Patent Application No. 10/092,993  
Attorney Docket No. 220445US

Proposed Claim Amendments

Claim 1 (currently amended): A maximum power point tracking method that ~~supplies for use in a system in which power~~ [[of]] from a direct-current power source, ~~having which has~~ a bow-shaped current-voltage characteristic, is supplied to a load via a switching converter, ~~wherein the method comprising:~~

performing low frequency, minute modulation of an output voltage of the direct-current power source;

detecting an output current value of said the direct-current power source, ~~which undergoes low frequency, minute modulation of input voltage to the switching converter,~~ is detected in a circuit ~~with~~ after performing the modulation, the circuit being configured to perform an amplification factor switching function that switches [[the]] an amplification factor of the circuit between definite magnitudes ~~synchronizing in~~ synchronization with said the performed modulation~~[[,]] to produce an output; and~~

controlling said switching converter ~~is controlled~~ using a signal obtained in a discriminator circuit by demodulating the output of [[this]] the discriminator circuit ~~synchronizing in synchronization~~ with said the performed modulation.

Claim 2 (currently amended): The maximum power point tracking method of claim 1, ~~that limits~~ further comprising:

limiting the input voltage of the switching converter to a predetermined range.

Claim 3 (original): The maximum power point tracking method of claim 1, wherein said direct current power source includes at least one of a solar cell, a direct-

current power source that generates power using wind power, and a direct-current power source that generates power using wave power.

Claim 4 (original): The maximum power point tracking method of claim 2, wherein said direct-current power source includes at least one of a solar cell, a direct-current power source that generates power using wind power, and a direct-current power source that generates power using wave power.

Claim 5 (currently amended): A maximum power point tracking device that supplies power of a direct-current power source, which has a bow-shaped current-voltage characteristic, to a load ~~via a switching converter~~, said maximum power point tracking device comprising:

(1) a first circuit for performing configured to perform low-frequency, minute modulation ~~that by alternately switches input~~ switching an output voltage of the ~~switching converter~~ direct-current power source between two voltage values;

(2) a second circuit that detects configured to detect an output current value of said the direct-current power source and ~~has to perform~~ an amplification factor switching function that switches ~~[[the]]~~ an amplification factor of the second circuit between definite magnitudes ~~synchronizing in~~ synchronization with the modulation ~~in~~ (1)-above performed by the first circuit;

(3) a ~~discriminator~~ third circuit for obtaining configured to obtain a component ~~synchronized of an output of the second circuit in~~ synchronization with the modulation ~~in~~ (1) performed by the first circuit of output of the circuit in (2); and

(4) a fourth circuit that uses configured to use an output of the third circuit in (3) to generate a signal that is ~~also input~~ transmitted to a switching converter control circuit.

Claim 6 (currently amended): The maximum power point tracking device of claim [[4]] 5, further comprising [[a]] the switching converter control circuit that limits, which is configured to limit the input voltage of the switching converter to a predetermined range.

Claim 7 (original): The maximum power point tracking device of claim 5, wherein the direct current power source is at least one of a solar cell, a direct-current power source that generates power using wind power, and a direct-current power source that generates power using wave power.

Claim 8 (original): The maximum power point tracking device of claim 6, wherein the direct current power source is at least one of a solar cell, a direct-current power source that generates power using wind power, and a direct-current power source that generates power using wave power.

I:\ATTY\CHY\220445\US\220445 PROP CLMS 08\JUN04.DOC